


HMR



Dimension



TYPE	DIMENSION (mm)								
	L (±1)	L2 (±1)	W1 (±0.2)	W2 (±0.2)	P1 (±0.2)	P2 (±0.2)	P3 (±1)	t1 (±0.1)	t2 (±0.1)
RQL-15	48	23	3	12.5	7	8	13	0.6	0.6
RQL-20	63	23	3	12.5	7	8	13	0.6	0.6
RQL-25	62	24	3	12.5	7	8	16	0.6	0.7
RQL-30	76	38	3	18	7	11	19	0.6	0.7
RQL-40	90	38	3	18	7	11	19	0.6	0.7

Specifications

TYPE	RATED WATTAGE(W)	RESISTANCE RANGE(Ω)
RQL-15	15W	0.5~500
RQL-20	20W	0.5~600
RQL-25	25W	0.5~700
RQL-30	30W	0.5~5K
RQL-40	40W	0.5~10K

Specifications

TOLERANCE

± 10% STANDARD, ± 5%, ALSO AVAILABLE.

OPERATING TEMPERATURE

-55℃ TO +275℃

TEMPERATURE COEFFICIENT


BELOW 1Ω 490 ~ 1300PPM/℃ (TYP)

1Ω AND ABOVE 490PPM/℃ (TYP)

TERMINAL STRENGTH

- 5LBS MINIMUM

HOW TO ORDER



'Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before your order and/or use.'