


HMR



Features

- FUSIBLE RESISTOR.
- GREAT SAFETY AGAINST SURGE.
- FLAME PROOF COATING.
- TOLERANCE FROM : $\pm 5\%$

Dimension



TYPE	DIMENSION (mm)			
	D (± 0.5)	L (± 2.0)	d (± 0.03)	I (± 1)
RW-FU	3 ± 0.5	9.0	0.6	25

TYPE	WATTAGE RATING(W)	RES. RANGE(Ω)
RW-FU	1W	CUSTOMER MADE

Performance

CHARACTERISTICS	LIMITS	TEST METHODOS
DC RESISTANCE	WITHIN SPECIFIED TOLERANCE	MEASURING A POINT 3/81 $\pm 1-16$ INCH FROM THE BODY
THERMAL SHOCK	THE CHANGE IN Ω SHALL NOT EXCEED $\pm (10\% + 10HM)$	A. SEQUENCE - - 55°C : 30MIN 25°C : 5MIN 85°C : 30MIN
SHORT-TIME OVERLOAD	SHALL BE NO EVIDENCE OF ARCING, BURNING OR CHARGING	1W ~ 3W $\rightarrow V = \sqrt{2.5} \cdot PR$ 5 SECONDS
SURGE LIMIT	OVER 6K VOLTAGE	

HOW TO ORDER

