



HMR



Dimension



TYPE	DIMENSION (mm)								
	L (±1)	W1 (±1)	W2 (±0.5)	W3 (±0.5)	W4 (±0.5)	H1 (±1)	H2 (±1)	H3 (±1)	P (±1)
RQB-05	27	9.5		1.5	1.5	9.5	13.5	29	14
RQD-05	27	9.5	5.5	8.5	1.5	9.5	15	29	14
RQB-07	35	9.5		1.5	1.5	9.5	13.5	29	21
RQD-07	35	9.5	5.5	8.5	1.5	9.5	15	29	21
RQB-10	48	9.5		1.5	1.5	9.5	13.5	29	34
RQD-10	48	9.5	5.5	8.5	1.5	9.5	15	29	34
RQB-15	48	12.5		1.5	1.5	12.5	13.5	31	34
RQD-15	48	12.5	5.5	8.5	1.5	12.5	15	31	34
RQB-20	62.5	12.5		1.5	1.5	12.5	13.5	31	46
RQD-20	62.5	12.5	5.5	8.5	1.5	12.5	15	31	46

Specifications

TYPE	RATED WATTAGE(W)	RESISTANCE RANGE(Ω)
RQB-05	5W	0.1~300
RQD-05	5W	0.1~300
RQB-07	7W	0.2~400
RQD-07	7W	0.2~400
RQB-10	10W	0.3~500
RQD-10	10W	0.3~500
RQB-15	15W	0.5~500
RQD-15	15W	0.5~500
RQB-20	20W	0.5~600
RQD-20	20W	0.5~600

Specifications


TOLERANCE
± 10% STANDARD, ± 5%, ALSO AVAILABLE.

OPERATING TEMPERATURE
- 55℃ TO + 275℃

TEMPERATURE COEFFICIENT
BELOW 1Ω 490 ~ 1300PPM/℃ (TYP)
1Ω AND ABOVE 490PPM/℃ (TYP)

TERMINAL STRENGTH
- 5LBS MINIMUM

HOW TO ORDER



Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before your order and/or use.