


HMR



Dimension



TYPE	DIMENSION (mm)				
	W(± 1)	D(± 1)	H(± 1)	P(± 0.5)	d(± 0.02)
RQR-02	11	7.5	20.5	5	0.8
RQR-03	12	8	25.5	5	0.8
RQR-05	13.5	9.5	26.5	5	0.8
RQR-07	14	10	40	5	0.8
RQR-10	16	12	34	7.5	0.8

Specifications

TYPE	RATED WATTAGE(W)	RESISTANCE RANGE(Ω)		
		GLASS CORE	MOR CORE	CERAMIC CORE
RQR-02	2W	0.1~50	50~200K	0.1~5K
RQR-03	3W	0.1~50	50~200K	0.1~5K
RQR-05	5W	0.1~150	80~250K	0.1~15K
RQR-07	7W	0.2~220	80~250K	0.1~15K
RQR-10	10W	0.3~200	200~250K	0.1~30K

Specifications

TOLERANCE

$\pm 10\%$ STANDARD, $\pm 5\%$, ALSO AVAILABLE.

TEMPERATURE COEFFICIENT

BELOW 1Ω 490 ~ 1300PPM/ $^{\circ}\text{C}$ (TYP)
 1Ω AND ABOVE 490PPM/ $^{\circ}\text{C}$ (TYP)

OPERATING TEMPERATURE

- 55 $^{\circ}\text{C}$ TO + 275 $^{\circ}\text{C}$

TERMINAL STRENGTH

- 5LBS MINIMUM

HOW TO ORDER

